

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



20 JAN 2005



(43) International Publication Date  
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number  
**WO 2004/007112 A1**

(51) International Patent Classification<sup>7</sup>: B22D 11/06,  
11/128

[IT/IT]; Via G. Paolini, 29, I-34070 Fogliano Redipuglia (IT). DE LUCA, Andrea [IT/IT]; Via Malignani, 13/6, I-33047 Remanzacco (IT). KAPAJ, Nuredin [AL/IT]; Via Caprera, 7, I-33100 Udine (IT). FAGGIANI, Edi [IT/IT]; Piazzale Cavedalis, 6/2, I-33100 Udine (IT).

(21) International Application Number:  
PCT/EP2003/007301

(74) Agent: GERVASI, Gemma; Notarbartolo & Gervasi S.p.A., Corso di Porta Vittoria, 9, I-20122 Milano (IT).

(22) International Filing Date: 8 July 2003 (08.07.2003)

(81) Designated States (national): AE, AG, AL, AM, AT, AU,

(25) Filing Language: English

AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

(26) Publication Language: English

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

(30) Priority Data:  
MI2002A001509 10 July 2002 (10.07.2002) IT

GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,

(71) Applicant (for all designated States except US): DANIELI & C. OFFICINE MECCANICHE S.P.A. [IT/IT]; Via Nazionale, 41, I-33042 Buttrio (IT).

LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,

(72) Inventors; and  
(75) Inventors/Applicants (for US only): POLONI, Alfredo

MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,


SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,

UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

{Continued on next page}

(54) Title: CONTINUOUS CASTING PLANT WITH A DEFLECTING DEVICE FOR METALLIC STRIPS AND DEFLECTING METHOD



(57) **Abstract:** A metallic strip mobile deflecting flap (5) of a metallic strip continuous casting plant is placed below the counter rotating roll ingot mould and deflects the initial section of the strip sending it horizontally towards the transport rolls (6). The device passes from a standby position, wherein it does not interfere with said metallic strip (N), and a position of interference with the metallic strip (N), wherein it deflects the strip in a horizontal direction. A method for deflecting the strip produced by continuous casting to a guided rolling pathway is also described.

**BEST AVAILABLE COPY**

WO 2004/007112 A1